

# Material Name CARBON DIOXIDE, GAS

# \* \* \*Section 1 - IDENTIFICATION\* \* \*

# Product Identifier: CARBON DIOXIDE, GAS

#### **Trade Names/Synonyms**

MTG SDS 17; CARBONIC ACID GAS; CARBONIC ANHYDRIDE; CARBON DIOXIDE; CARBON OXIDE; UN

1013; CO2

# **Chemical Family**

inorganic, gas

#### **Recommended Use**

Industrial and Specialty Gas Applications

#### **Restrictions on Use**

None known.

#### **Manufacturer Information**

MATHESON TRI-GAS, INC. 150 Allen Road, Suite 302 Basking Ridge, NJ 07920 General Information: 1-800-416-2505

Emergency #: 1-800-424-9300 (CHEMTREC)
Outside the US: 703-527-3887 (Call collect)

**SDS ID: MAT04260** 

# \* \* \*Section 2 - HAZARDS IDENTIFICATION\* \* \*

#### Classification in accordance with 29 CFR 1910.1200

Gas under pressure, Compressed gas

Specific Target Organ Toxicity - Single Exposure, Category 3 (central nervous system)

#### **GHS LABEL ELEMENTS**

#### Symbol(s)



#### Signal Word

WARNING

#### **Hazard Statement(s)**

Contains gas under pressure; may explode if heated

May cause drowsiness and dizziness

May displace oxygen and cause rapid suffocation.

# **Precautionary Statement(s)**

#### **Prevention**

Avoid breathing gas. Use only outdoors or in a well-ventilated area.

### Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**SDS ID: MAT04260** 

#### Material Name CARBON DIOXIDE, GAS

#### **Storage**

Protect from sunlight. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

### **Disposal**

Dispose in accordance with all applicable regulations.

#### Hazard(s) Not Otherwise Classified

May cause frostbite upon sudden release of compressed gas.

#### \* \* \*Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS\* \* \*

CAS	Component	Percent
124-38-9	Carbon dioxide	100

#### **Component Related Regulatory Information**

This product may be regulated, have exposure limits or other information identified as the following: Carbon dioxide and ethylene oxide mixtures (8070-50-6).

# \* \* \*Section 4 - FIRST AID MEASURES\* \* \*

#### **Description of Necessary Measures**

#### Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

#### Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

### Eyes

Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Then get immediate medical attention.

#### Ingestion

If swallowed, get medical attention.

#### **Most Important Symptoms/Effects**

#### **Acute**

suffocation, frostbite, central nervous system depression

#### **Delayed**

No information on significant adverse effects.

# Indication of Immediate Medical Attention and Special Treatment

For inhalation, consider oxygen.

# \* \* \*Section 5 - FIRE FIGHTING MEASURES\* \* \*

#### **Suitable Extinguishing Media**

carbon dioxide, regular dry chemical, water spray, foam

#### **Unsuitable Extinguishing Media**

Do not direct water at source of leak or safety devices; icing may occur.

#### **Specific Hazards Arising from the Chemical**

Negligible fire hazard. Containers may rupture or explode if exposed to heat.

#### **Hazardous Combustion Products**

Combustion: oxides of carbon

#### Material Name CARBON DIOXIDE, GAS

#### **Fire Fighting Measures**

Use extinguishing agents appropriate for surrounding fire. Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile). Do not get water directly on material. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

**SDS ID: MAT04260** 

#### **Special Protective Equipment and Precautions for Firefighters**

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

# \* \* \*Section 6 - ACCIDENTAL RELEASE MEASURES\* \* \*

#### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

#### Methods and Materials for Containment and Cleaning Up

Stop leak if possible without personal risk. Do not touch or walk through spilled material. Use water spray to reduce vapors or divert vapor cloud drift. Do not direct water at spill or source of leak. If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate. Ventilate closed spaces before entering. Stay upwind and keep out of low areas.

# \* \* \*Section 7 - HANDLING AND STORAGE\* \* \*

#### **Precautions for Safe Handling**

Avoid breathing gas. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling.

#### Conditions for Safe Storage, including any Incompatibilities

Store and handle in accordance with all current regulations and standards. Protect from physical damage. Store in a well-ventilated area. Keep container tightly closed. Protect from sunlight. Store locked up. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.

**Incompatibilities** combustible materials, oxidizing materials, metal salts, reducing agents, metal carbide, metals, bases

# \* \* \*Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION\* \* \*

#### **Component Exposure Limits**

#### Carbon dioxide (124-38-9)

**ACGIH:** 5000 ppm TWA

30000 ppm STEL

Europe: 5000 ppm TWA; 9000 mg/m3 TWA
OSHA (Final): 5000 ppm TWA; 9000 mg/m3 TWA
OSHA (Vacated): 10000 ppm TWA; 18000 mg/m3 TWA

30000 ppm STEL; 54000 mg/m3 STEL

**NIOSH:** 5000 ppm TWA; 9000 mg/m3 TWA

30000 ppm STEL; 54000 mg/m3 STEL

#### **Component Biological Limit Values**

There are no biological limit values for any of this product's components.

**IDLH** 

40,000 ppm

#### **Appropriate Engineering Controls**

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

#### Material Name CARBON DIOXIDE, GAS

# Individual Protection Measures, such as Personal Protective Equipment Eyes/Face Protection

For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

**SDS ID: MAT04260** 

#### **Skin Protection**

For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.

#### **Glove Recommendations**

Wear insulated gloves.

#### **Respiratory Protection**

The following respirators and maximum use concentrations are drawn from NIOSH and/or OSHA.

40,000 ppm

Any supplied-air respirator.

Any self-contained breathing apparatus with a full facepiece.

Emergency or planned entry into unknown concentrations or IDLH conditions -

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Escape -

Any appropriate escape-type, self-contained breathing apparatus.

# \* \* \*Section 9 - PHYSICAL AND CHEMICAL PROPERTIES\* \* \*

 Physical State:
 Gas
 Appearance:
 Colorless gas

 Color:
 colorless
 Physical Form:
 compressed gas

 Odor:
 odorless
 Odor Threshold:
 Not available

Odor:odorlessOdor Threshold:Not availableTaste:acid tastepH:acidic in solutionPoint:-57 °C @4000 mmHgBoiling Point:-78.5 °C (sublimation)

Melting/Freezing Point:-57 °C @4000 mmHgBoiling Point:-78.5 °C (sublimationFlash Point:not flammableDecomposition:Not available

Evaporation Rate: Not available LEL: Not available

UEL: Not available Vapor Pressure: 43700 mmHg @ 21 °C

Vapor Density (air = 1):1.5Specific Gravity (water=1):1.527 @ 21 °CWater Solubility:SolubleLog KOW:Not available

Auto Ignition:Not availableViscosity:14.9 uPa-sec @ 25 °CSublimation Point:-78.5 °CTriple Point:-56.6 °C @ 3883.6 mmHg

Volatility by Volume:100 %Molecular Weight:44.01Molecular Formula:C-O2Critical Temperature:304.13 K

Flammability (solid, gas): Not flammable

#### **Other Property Information**

No additional information is available.

**Solvent Solubility** 

Soluble: alcohol, acetone, hydrocarbons, organic solvents

Page 4 of 8 Issue Date 12/10/2014 Revision 2.0100 Print Date: 12/10/2014

**SDS ID: MAT04260** 

#### Material Name CARBON DIOXIDE, GAS

### \* \* \*Section 10 - STABILITY AND REACTIVITY\* \* \*

#### Reactivity

No reactivity hazard is expected.

#### **Chemical Stability**

Stable at normal temperatures and pressure.

#### **Possibility of Hazardous Reactions**

Will not polymerize.

#### **Conditions to Avoid**

Protect from physical damage and heat. Containers may rupture or explode if exposed to heat. Avoid contact with water or moisture.

#### **Incompatible Materials**

combustible materials, oxidizing materials, metal salts, reducing agents, metal carbide, metals, bases

#### **Hazardous Decomposition**

Combustion: oxides of carbon

# \* \* \*Section 11 - TOXICOLOGICAL INFORMATION\* \* \*

#### **Acute and Chronic Toxicity**

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and no selected endpoints have been identified

# **RTECS Acute Toxicity (selected)**

The components of this material have been reviewed, and RTECS publishes the following endpoints:

#### Carbon dioxide (124-38-9)

Inhalation: 361 gm/m3/2 hour Inhalation Mouse LC50; 200000 ppm/2 hour Inhalation Mouse LC50

#### **Acute Toxicity Level**

# Carbon dioxide (124-38-9)

Non Toxic: inhalation

#### Information on Likely Routes of Exposure

#### Inhalation

sensitivity to light, changes in blood pressure, nausea, irregular heartbeat, headache, drowsiness, dizziness, disorientation, sleep disturbances, emotional disturbances, tingling sensation, tremors, muscle cramps, visual disturbances, suffocation, convulsions, unconsciousness, coma, difficulty breathing, blood disorders

#### Ingestion

ingestion of a gas is unlikely

#### **Skin Contact**

blisters, frostbite

# **Eye Contact**

irritation, blurred vision, frostbite

#### **Immediate Effects**

suffocation, frostbite, central nervous system depression

#### **Delayed Effects**

No information on significant adverse effects.

# **Medical Conditions Aggravated by Exposure**

heart or cardiovascular disorders, respiratory disorders

# Irritation/Corrosivity Data

No data available.

**SDS ID: MAT04260** 

#### Material Name CARBON DIOXIDE, GAS

#### **RTECS Irritation**

The components of this material have been reviewed and RTECS publishes no data as of the date on this document.

#### **Target Organs**

#### Carbon dioxide (124-38-9)

central nervous system

#### **Respiratory Sensitization**

No test data available.

#### **Dermal Sensitization**

No data available.

#### Carcinogenicity

#### **Component Carcinogenicity**

None of this product's components are listed by ACGIH, IARC, NTP, OSHA or DFG.

#### **Mutagenic Data**

No data available.

#### **RTECS Reproductive Effects**

The components of this material have been reviewed, and RTECS publishes the following endpoints:

#### Carbon dioxide (124-38-9)

55 pph Inhalation Mouse TCLo (4 hour, 6 day(s)); 55 pph Inhalation Mouse TCLo (2 hour, 3 day(s)); 2 pph Inhalation Mouse TCLo (8 hour, pregnant 10 day(s)); 13 pph Inhalation Rabbit TCLo (4 hour, pregnant 9-12 day(s)); 6 pph Inhalation Rat TCLo (24 hour, pregnant 10 day(s)); 6 pph Inhalation Rat TCLo (24 hour, pregnant 10 day(s))

#### **Tumorigenic Data**

No data available.

### **Specific Target Organ Toxicity - Single Exposure**

central nervous system

#### **Specific Target Organ Toxicity - Repeated Exposure**

No target organs identified.

# **Aspiration Hazard**

Not applicable.

# \* \* \*Section 12 - ECOLOGICAL INFORMATION\* \* \*

#### **Component Analysis - Aquatic Toxicity**

No LOLI ecotoxicity data are available for this product's components.

#### Persistence and Degradability

No data available.

#### **Bioaccumulative Potential**

No data available.

#### **Mobility**

No data available.

# \* \* \*Section 13 - DISPOSAL CONSIDERATIONS\* \* \*

#### **Disposal Methods**

Dispose in accordance with all applicable regulations.

#### **Component Waste Numbers**

The U.S. EPA has not published waste numbers for this product's components.

### Material Name CARBON DIOXIDE, GAS

\* \* \*Section 14 - TRANSPORT INFORMATION\* \* \*

**SDS ID: MAT04260** 

#### **US DOT Information**

**Shipping Name:** Carbon dioxide **UN/NA #:** UN1013 **Hazard Class:** 2.2

Required Label(s): 2.2

#### **IMDG** Information

**Shipping Name:** Carbon dioxide **UN #:** UN1013 **Hazard Class:** 2.2

Required Label(s): 2.2

# \* \* \*Section 15 - REGULATORY INFORMATION\* \* \*

#### **Component Analysis**

# **U.S. Federal Regulations**

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

# SARA 311/312 Hazardous Categories

Acute Health: Yes Chronic Health: No Fire: No Pressure: Yes Reactive: No

#### **U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Carbon dioxide	124-38-9	Yes	Yes	Yes	Yes	Yes

Not regulated under California Proposition 65

#### **Component Analysis - Inventory**

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
Carbon dioxide	124-38-9	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes

#### \* \* \*Section 16 - OTHER INFORMATION\* \* \*

NFPA Ratings: Health: 3 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Page 7 of 8 Issue Date 12/10/2014 Revision 2.0100 Print Date: 12/10/2014

**SDS ID: MAT04260** 

#### Material Name CARBON DIOXIDE, GAS

# Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU -Australia: BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR -Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation: DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR -New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID -European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US -**United States** 

#### Other Information

Matheson Tri-Gas, Inc. makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Matheson Tri-Gas, Inc. shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.

End of Sheet MAT04260