

Safety Data Sheet

Skilcraft Power Duster II, 10 oz

SDS Revision Date:

08/23/2018



1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity

Skilcraft Power Duster II, 10 oz

Alternate Names

LHB Part Number: 0894----011, 0894---014
NSN: 6850-01-517-1506, 6850-01-412-0040
CAGE Code: 0FTT5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

See product label.

Application Method

See product label.

1.3. Details of the supplier of the safety data sheet

Company Name

LHB Industries
8833 Fleischer Place
Berkeley, MO 63134

Emergency

24 hour Emergency Telephone No.

(800) 633-8253 (PERS)

Customer Service: LHB Industries

(314) 423-4333

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Liquified Gas;H280

Contains gas under pressure; may explode if heated.

Simple Asphyxiant

May displace oxygen and cause rapid suffocation.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Warning

H280 Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Safety Data Sheet

Skilcraft Power Duster II, 10 oz

SDS Revision Date:

08/23/2018



[Prevention]:

No GHS prevention statements

[Response]:

No GHS response statements

[Storage]:

P410+403 Protect from sunlight. Store in a well ventilated place.

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1,1,1,2-Tetrafluoroethane (HFC-134a) CAS Number: 0000811-97-2	100	Liquified Gas;H280 Simple Asphyxiant	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General

Move victim to fresh air.
Call 911 or emergency medical service if deemed necessary.
Give artificial respiration if victim is not breathing.
Administer oxygen if breathing is difficult.
Remove and isolate contaminated clothing and shoes.
In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
Keep victim warm and quiet.
Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Safety Data Sheet

Skilcraft Power Duster II, 10 oz

SDS Revision Date:

08/23/2018



Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove and isolate contaminated clothing and shoes. Clothing frozen to the skin should be thawed before being removed. In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	Liquid and gas under pressure, overheating and overpressurizing may cause gas release or rupturing of container. May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products. Vapor reduces oxygen available for breathing and is heavier than air. Harmful if inhaled and may cause heart irregularities, unconsciousness or death. Liquid contact with eyes or skin may cause frostbite. Potential Health Effects Inhalation and skin contact are expected to be the primary routes of occupational exposure to this material. As with most liquefied gases, contact with rapidly volatilizing liquid or cold vapor can cause frostbite to any tissue. High vapor concentrations are irritating to the eyes and respiratory tract and may result in central nervous system effects such as headache, dizziness, anesthesia, drowsiness, and in severe exposure, loss of consciousness and death. The dense vapor of this material may reduce the available oxygen for breathing and produce symptoms such as headache, dizziness, drowsiness, cyanosis and lack of muscle control followed by collapse. Prolonged exposure to an oxygen-deficient atmosphere may be fatal. Inhalation of this material may cause an increase in the sensitivity of the heart to adrenaline, which could result in irregular or rapid heartbeats and reduced heart function. Workers with heart disease or compromised heart function should limit exposure to this material. See section 2 for further details.
-----------------	--

5. Fire-fighting measures

5.1. Extinguishing media

Fire involving Tanks: Some of these materials, if spilled, may evaporate leaving a flammable residue. Some of these materials, if spilled, may evaporate leaving a flammable residue.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hydrogen fluoride, hydrogen chloride, carbon monoxide carbon dioxide and chlorine.

5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).

Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Structural firefighters' protective clothing will only provide limited protection.

Some may burn but none ignite readily.

Containers may explode when heated.

Ruptured cylinders may rocket.

Vapors may cause dizziness or asphyxiation without warning.

Vapors from liquefied gas are initially heavier than air and spread along ground.

Safety Data Sheet

Skilcraft Power Duster II, 10 oz

SDS Revision Date:

08/23/2018



Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
Fire may produce irritating, corrosive and/or toxic gases.

ERG Guide No. 126

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Do not touch or walk through spilled material.

Stop leak if you can do it without risk.

Do not direct water at spill or source of leak.

Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.

If possible, turn leaking containers so that gas escapes rather than liquid.

Prevent entry into waterways, sewers, basements or confined areas.

Allow substance to evaporate.

Ventilate the area.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Stay upwind.

Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Keep out of low areas.

Ventilate closed spaces before entering.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store this product below 120°F, in a cool, dry, well ventilated area away from heat, sparks, flame, oxidizers and out of direct sunlight.

Incompatible materials: Finely divided metals. Can react violently if in contact with alkali or alkaline earth metals such as sodium, potassium or barium.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

Safety Data Sheet

Skilcraft Power Duster II, 10 oz

SDS Revision Date:

08/23/2018



8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000811-97-2	1,1,1,2-Tetrafluoroethane (HFC-134a)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000811-97-2	1,1,1,2-Tetrafluoroethane (HFC-134a)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

- Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
- Eyes** Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.
- Skin** Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact.
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

Safety Data Sheet

Skilcraft Power Duster II, 10 oz

SDS Revision Date:

08/23/2018



9. Physical and chemical properties

Appearance	Colorless Liquefied Gas
Odor	Slight Ethereal Odor
Odor threshold	Not Measured
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	Nonflammable
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: N/A Upper Explosive Limit: N/A
Vapor pressure (Pa)	80.0 psig @ 77 F
Vapor Density	Heavier than air
Specific Gravity	1.245 @ 77F (Density 10.38 lb/gal)
Solubility in Water	Slight
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC %	0% by wt., 0 g/L
HAPS (lbs/gal)	None
HAPS (lbs/gal of Solids)	None
HAPS (lbs/lb of Solids)	None
% Volatile (by volume)	Not Measured

9.2. Other information

No other relevant information.

Safety Data Sheet

Skilcraft Power Duster II, 10 oz

SDS Revision Date:

08/23/2018



10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Do not expose to heat or store at temperature above 120°F.

10.5. Incompatible materials

Finely divided metals. Can react violently if in contact with alkali or alkaline earth metals such as sodium, potassium or barium.

10.6. Hazardous decomposition products

Hydrogen fluoride, hydrogen chloride, carbon monoxide carbon dioxide and chlorine.

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
1,1,1,2-Tetrafluoroethane (HFC-134a) - (811-97-2)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable

Safety Data Sheet

Skilcraft Power Duster II, 10 oz

SDS Revision Date:

08/23/2018



Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
1,1,1,2-Tetrafluoroethane (HFC-134a) - (811-97-2)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Safety Data Sheet

Skilcraft Power Duster II, 10 oz

SDS Revision Date:

08/23/2018



14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN3159	UN3159	UN3159
14.2. UN proper shipping name	UN3159, 1,1,1,2-Tetrafluoroethane Limited Quantity, 2.2,	1,1,1,2-Tetrafluoroethane, Limited Quantity	1,1,1,2-Tetrafluoroethane, Limited Quantity
14.3. Transport hazard class(es)	DOT Hazard Class: 2.2	IMDG: 2.2	Air Class: 2.2
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user			
	No further information		

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.		
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.		
WHMIS Classification	A		
US EPA Tier II Hazards	Fire:	No	
	Sudden Release of Pressure:	Yes	
	Reactive:	No	
	Immediate (Acute):	No	
	Delayed (Chronic):	No	
EPCRA 311/312 Chemicals and RQs:			
(No Product Ingredients Listed)			
EPCRA 302 Extremely Hazardous :			
(No Product Ingredients Listed)			
EPCRA 313 Toxic Chemicals:			
(No Product Ingredients Listed)			
Proposition 65 - Carcinogens (>0.0%):			
(No Product Ingredients Listed)			

Safety Data Sheet

Skilcraft Power Duster II, 10 oz

SDS Revision Date:

08/23/2018



Proposition 65 - Developmental Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

(No Product Ingredients Listed)

Penn RTK Substances (>1%) :

(No Product Ingredients Listed)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H280 Contains gas under pressure; may explode if heated.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document